## GOLEM



Optimally meeting all requirements of birth assistants and the mother, the GOLEM birth table enables birth in the standard position, with bent knees or in the knee-breast position, as well as necessary procedures. A high level of the operator's and mother's safety and operating hygiene is ensured by covering of all parts of the table with grey plastic casings.

The table is mobile and it features comfortable seamless washable upholstery in a colour of your choice. The table surface with a width of 600 mm is divided into a leg, middle, back and manually adjustable head segment. The positions, including an anti-shock position (Trendelenburg), are set by electric drives and can be set even if the table is fully loaded. The carrying capacity of the table is 150 kg. The table is equipped with electronics enabling the user to program 3 operating positions that are automatically set using a relevant pedal. This feature allows for easy switching between table positions without time delays. The optimal dividing of the surface allows for easy setting of the table to the position for birth and stitching and, after the leg segment is installed, to the lying position, in which a flat surface of 1 800 mm in length is created. The leg segment can be pushed to the low position before birth. Lengths of the segments: seat 400 mm, backrest 500 mm, head 400 mm, additional legs 500 mm.

The table is fully equipped: EUROrails for the fastening of accessories around the seat and backrest, removable polyurethane Goepel leg supports with a jointed fixture and fastening straps, foot step with a non-slip finish, stainless bowl, removable hand rails for the mother, paper roll holder to be used for the whole surface, the backrest and the seat, or for the seat only, infusion holder, Hand holder used during infusion.

WWW.GOLEMTABLE.COM

## WWW.GOLEMKRESLA.SK

## Birth table GOLEM Code Nr. G 06 60



All elements can be easily and comfortably adjusted and removed from the table, which means that the patient can also get on from the side. Electric drive adjustable height of 640 - 940 mm, electric drive adjustable back tilt of 0° to +80°, manually adjustable head segment tilt of  $\pm$  30°, electric drive adjustable seat (Trendelenburg) tilt of 0° to +30°. The table is equipped with electronics enabling the user to program



3 operating positions that are automatically set using a respective button. This feature allows for easy switching between the initial and operating positions of the table without time delays. The build-in dimensions of the table are approx.  $800 \times 1400$  mm. The weight of the table is 118 kg, the carrying capacity is 150 kg.





**ACCESSORIES:** Built-in battery with a fully automatic charger

Code Nr. D 06 40

