GOLEM



GOLEM ENT operating table is specially designed for operation in ophthalmology, ENT, dermatology and plastic surgery. Doctors in these fields will be maximally satisfy with some specific adjustments to this model.

The work area is divided into 4 segments (legs, seat, back, head) and is adjustable in height and Trendelenburg position. Also inclinations foot, the back and the head segment is adjusted electrically. All these moves are executed by five silent, reliable electric LINAK motors, controlled by hand control. The table is equipped with electronic memories of 4 positions that can be easily accessed by pressing a button (for example, the starting position, work location, location, 0")

Positioning of segments is performed. Wide range of positions allows the patient to be seated in a sitting position and adjusting positions to working position effortlessly. The head segment allows the lean forward/back and can also adjust the height of the patient. On head segment is placed removable and adjustable support of the doctor's forearm.

The table has a fixed and stable stainless steel construction, washable and disinfected desktop with trim black antistatic leatherette. Around EUROrails segments are placed for fastening of any accessory.

The standard version of the table is mobile with centrally braked castors \emptyset 100 mm. Power is from a standard electric socket, but the table is equipped with a built-in fully automatic charger and maintenance-free batteries in case of power failure.





GOLEM 4 T for ENT Code Nr. G 50 14 Operating table for ofthalmo/ENT/plastic surgery





ACCESSORIES:

Handrails for pacient on EUROrail D 50 30 Dual control of head segment by pedals and hand control D 50 31

TECHNICAL PARAMETRES:

Overal table length

Weight of table

Operating surface width Operating surface width include EUROrails	640 mm 670 mm
Lengths of the segments: Head Back Seat Leg	265 mm 650 mm 550 mm 510 mm
Lowest position of table Electric drive adjustable lift Electric drive adjustable trendelenburg	580 mm 300 mm 20°
Electric drive adjustable of: Head Back Leg	± 35° 0° + 70° 0° - 90°
Permissible loading of the operating surface	150 kg (total load)



2030 mm

115 kg